

Blank Inflatable pipe stopper 1.5 bar



- Made of high quality rubber with fabric insert
- Secure proofing of pipes in the range of canals
 - Temperature range from -20° to +80° C
 - Maximum test pressure in the pipe 0.5,
 - From DN 650 max. Test pressure 0.3 Bar

Part Number	Nominal Size (MM)	Product Normal Length (MM)	Min. Pipe Diameter (MM)	Required Inflation Pressure (Bar)	Product Weight (Kg)
AB50100	DN 50 - 100	330	45	1,5	0,4
AB70150	DN 70 - 150	370	64	1,5	0,6
AB100200	DN 100 - 200	550	88	1,5	1,2
AB150300	DN 150 - 300	550	138	1,5	2,1
AB200400	DN 200 - 400	650	185	1,5	3,1
AB200500	DN 200 - 500	800	185	1,5	4,5
AB3000600	DN 300 - 600	850	285	1,5	9,5
AB5001000	DN 500 - 1000	1150	485	1,5	26,5
AB6001200	DN 600 - 1200	1300	585	1,5	35,0
AB6001600	DN 600 - 1600	1900	575	1,5	43,0
AB8002000	DN 800 - 2000	2400	790	1,5	90,0

Blank Inflatable pipe stopper 2.5 bar



- Made of high quality rubber with fabric insert
- Secure proofing of pipes in the range of canals
 - Temperature range from -20° to +80° C
 - Maximum test pressure in the pipe 1.0
 - From DN 650 max. Test pressure 0.8 Bar

Part Number	Nominal Size (MM)	Product Normal Length (MM)	Min. Pipe Diameter (MM)	Required Inflation Pressure (BAR)	Product Weight (KG)
KAB3570	DN 35 - 70	300	33	2,5	0,2
KAB50100	DN 50 - 100	330	45	2,5	0,4
KAB70150	DN 70 - 150	370	64	2,5	0,6
KAB100200	DN 100 - 200	550	88	2,5	1,2
KAB150300	DN 150 - 300	550	138	2,5	2,1
KAB200400	DN 200 - 400	650	185	2,5	3,1
KAB300600	DN 300 - 600	850	285	2,5	9,5
KAB5001000	DN 500 - 1000	1150	485	2,5	26,5
KAB6001200	DN 600 - 1200	1300	585	2,5	35,0