

Conical Pipe Plug



Description

Pipe Plug is reinforced of hot vulcanize brand new type of deafening rubber goods, based on the frameless type pneumatic pillows but with more flexible inflatable structure. That allows entering the plug through small opening hole are both vertical and horizontal. Such flexibility allows you to work with a wide range of pipes diameters.

Part Number	Nominal Size [MM]	Product Normal Length [MM]	Min. Pipe Diameter [MM]	Max. Pipe Diameter [MM]	Required Inflation Pressure [bar]	Product Weight [Kg]
CSP702001	DN 70 - 200	100/400	70	200	1	1.0
CSP1004001	DN 100 - 400	200/850	100	400	1	2.5
CSP2006001	DN 200 - 600	300/1000	200	600	1	6.0
CSP3008001	DN 300 - 800	400/1300	300	800	1	9.6
CSP40010001	DN 400 - 1000	500/1600	400	1000	1	14.2
CSP50012001	DN 500 - 1200	600/1900	500	1200	1	19.1
CSP50014001	DN 500 - 1400	700/1900	500	1400	1	29.1
CSP50015001	DN 500 - 1500	750/2600	500	1800	1	32.2
CSP60016001	DN 600 - 1600	800/2700	600	1600	1	35.2
CSP80018001	DN 800 - 1800	900/3100	800	1800	1	42.2
CSP100022001	DN 1000 - 2200	1100/3400	1000	2200	1	85.3
CSP150028001	DN 1500 - 2800	1400/3900	1500	2800	1	132.3
CSP180032001	DN 1800 - 3200	1600/4250	1800	3200	1	182.3
CSP220036001	DN 2200 - 3600	1800/4500	2200	3600	1	220.4

ALSO AVAILABLE
WITH A 2" OR 2 ½"
BYPASS