

# Flexible packer

with bypass and chassis

- for the rehabilitation of pipes and channels
- made of high quality rubber with fabric insert
- temperature range from -20° to +80° C
- easy handling due to chassis with 3 wheels at both ends



Part Number	Nominal Size [MM]	Product Normal Length [MM]	Cylinder- Length [MM]	Min. Pipe Diameter [mm]	Min. contact Length [MM]	Required Inflation Pressure [bar]	Product Weight [Kg]
FWP10015010	DN 100 - 150	1.350	1.000	63	830	2,5	2,3
FWP10015015	DN 100 - 150	1.850	1.500	63	1.330	2,5	3,2
FWP10015020	DN 100 - 150	2.350	2.000	63	1.830	2,5	4,0
FWP10015025	DN 100 - 150	2.850	2.500	63	2.330	2,5	4,9
FWP10015030	DN 100 - 150	3.350	3.000	63	2.830	2,5	5,7
FWP10015040	DN 100 - 150	4.350	4.000	63	3.830	2,5	7,4
FWP10015050	DN 100 - 150	5.350	5.000	63	4.830	2,5	9,1
FWP15025010	DN 150 - 250	1.350	1.000	103	775	2,0	4,5
FWP15025015	DN 150 - 250	1.850	1.500	103	1.275	2,0	6,1
FWP15025020	DN 150 - 250	2.350	2.000	103	1.775	2,0	7,8
FWP15025025	DN 150 - 250	2.850	2.500	103	2.275	2,0	9,4
FWP15025030	DN 150 - 250	3.350	3.000	103	2.775	2,0	11,1
FWP15025040	DN 150 - 250	4.350	4.000	103	3.775	2,0	14,4
FWP15025050	DN 150 - 250	5.350	5.000	103	4.775	2,0	17,7
FWP20030010	DN 200 - 300	1.350	1.000	148	720	2,0	7,3
FWP20030015	DN 200 - 300	1.850	1.500	148	1.220	2,0	10,0
FWP20030020	DN 200 - 300	2.350	2.000	148	1.720	2,0	12,7
FWP20030030	DN 200 - 300	3.350	3.000	148	2.720	2,0	18,1
FWP20030040	DN 200 - 300	4.350	4.000	148	3.720	2,0	23,5
FWP20030050	DN 200 - 300	5.350	5.000	148	4.720	2,0	28,9
FWP30040010	DN 300 - 400	1.350	1.000	210	700	1,5	9,9
FWP30040015	DN 300 - 400	1.850	1.500	210	1.200	1,5	13,5
FWP30040020	DN 300 - 400	2.350	2.000	210	1.700	1,5	17,2
FWP30040030	DN 300 - 400	3.350	3.000	210	2.700	1,5	24,5
FWP30040040	DN 300 - 400	4.350	4.000	210	3.700	1,5	31,8
FWP30040050	DN 300 - 400	5.350	5.000	210	4.700	1,5	39,0
FWP40060015	DN 400 - 600	1.850	1.500	340	1.200	1,0	21,5
FWP40060020	DN 400 - 600	2.350	2.000	340	1.700	1,0	27,3
FWP40060030	DN 400 - 600	3.350	3.000	340	2.700	1,0	38,9
FWP40060040	DN 400 - 600	4.350	4.000	340	3.700	1,0	50,5
FWP40060050	DN 400 - 600	5.350	5.000	340	4.700	1,0	62,1
FWP600800XX	ON ENQUIRY	1,500	- 5,000				